

<b>DATA SHEET</b>	<b>CO2 SLAVE VALVE - SINGLE PIECE UNIT</b>				PART NO: B462
DP-5.8/11-439	DATE : SEP-2011	REVISION : 00	SCALE : N.T.S	SHEET : 1 OF 1	APPD. BY: DB

INTRODUCTION :-

CEODEUX SLAVE CYLINDER VALVE FITTED IN THE CO2 CYLINDER CAN BE OPERATED THROUGH PNEUMATIC PRESSURE HEAD WHICH IS AN INTEGRAL PART OF VALVE.



**TECHNICAL SPECIFICATION**

01.	MANUFACTURER	CEODEUX (EU)	06.	INLET CONNECTION	C= 25E EN 629-1
02.	MAX. WORKING PRESSURE	250 BAR	07.	OUTLET CONNECTION	A= W21,8X1/14" DIN477
03.	WORKING TEMPERATURE RANGE	-20°C + 60°C	08.	DIP TUBE CONNECTION	G= M16 X 1
04.	SEAT ORIFICE SIZE	12MM	09.	LEVER CONNECTION	M10
05.	MATERIAL OF COMPONENT	BRASS	10.	APPROVAL	CE

IMPORTANT:

AGNI CONTROLS RESERVES THE RIGHT TO CHANGE OR MODIFY WITHOUT PREVIOUS NOTICE ANY DATA OR SPECIFICATION DUE TO CHANGES OR MODIFICATION IN ORDER TO IMPROVE THE PRODUCTS / SYSTEM PRESENTED.



**AGNI CONTROLS CHENNAI**  
NO.1, 6TH STREET, Dr.SUBBARAYAN NAGAR,  
KODAMBAKKAM, CHENNAI-600 024, INDIA.

PHONE : +91 44 2481 2420, FAX : +91 44 2481 2475,

E-MAIL : engineering@agnicontrols.com WEBSITE : www.balafire.com

**ISO 9001 - 2008  
CERTIFIED BY  
BUREAU VERITAS**