

DATA SHEET

AIR PURGING UNIT

PART NO: IH323

OLD DWG.NO.:DP-5.8/08-087 DATE :MAR. 2008 NEW DOC.NO.: DP-5.8/MT-044 DATE : FEB. 2013


REVISION: 00 SCALE: N.T.S SHEET: 1 OF 1


APPD. BY



INTRODUCTION :-

AIR BLOWER WITH SUITABLE ELECTRICAL & HOSE CONNECTION IS USED FOR AIR PURGING APPLICATION TO CLEAN FLAME / EMBER DETECTOR. THE UNIT IS FOR STAND ALONE APPLICATION. WORK ON 230V AC WITH REMOTE START PROVISION. START OF BLOWER IS MANUAL, STOP OF BLOWER IS AUTOMATIC AFTER 1 MINUTE OPERATION. NOTE: THIS DATASHEET CAN BE ALSO REFERRED AS NEW DOC.NO.: DP-5.8/CP-044





REMOTE START (USE ONLY PUSH TO ON SWITCH)

- 1. TOLERANCE ON DIMENSION \pm 3 mm, UNLESS OTHERWISE SPECIFIED.
- 2. ALL DIMENSIONS ARE IN "mm" UNLESS OTHERWISE SPECIFIED.
- 3. SUITABLE TO CLEAN MAXIMUM NO. OF 2 DETECTORS SIMULTANEOUSLY BY USING T' ADAPTER.
- 4. USE ADAPTER TO CONNECT DIRECTLY ON DETECTOR.
- 5. TO BE FIXED PERMANENTLY.
- 6. TO BE PROTECTED FROM RAIN AND WIND.
- 7. FILTER IS TO BE CLEANED PERIODICALLY AS PER SITE REQUIREMENT.

TECHNICAL SPECIFICATION **MECHANICAL ELECTRICAL** INPUT SUPPLY VOLTAGE 230V AC ±10% **MANUFACTURER** AGNI CONTROLS - CHENNAI 02. POWER CONSUMPTION 550 W 02. CONSTRUCTION (ENCLOSURE) 1.2mm CR SHEET 03. REMOTE OPERATION TERMINAL IS PROVIDED TO 03. PAINT SHADE L GRAY CONNECT PUSH TO CLOSE OVER ALL DIMENSION 250(L) X 220(W) X 200(H) PUSH BUTTON STATION (WITHOUT HOLDING) 05. AIR PRESSURE 5.5 KPa MANUAL START, AUTO STOP BLOWER OPERATION $3.8 \text{ M}^3/\text{MIN}$ 06. OUTLET AIR VOLUME AFTER 1 MINUTE.

IMPORTANT:

AGNI CONTROLS RESERVES THE RIGHT TO CHANGE OR MODIFY WITHOUT PREVIOUS NOTICE ANY DATA OR SPECIFICATION DUE TO CHANGES OR MODIFICATION IN ORDER TO IMPROVE THE PRODUCTS/SYSTEM PRESENTED.



FLAME / EMBER DETECTOR

CERTIFIED BY BUREAU VERITAS

ISO 9001 - 2008

RIGHT SIDE VIEW

NO.1, 6TH STREET, Dr.SUBBARAYAN NAGAR, KODAMBAKKAM, CHENNAI-600 024, INDIA.

PHONE: +91 44 2481 2420, FAX: +91 44 2481 2475, E-MAIL : engineering@agnicontrols.com WEBSITE : www.balafire.com